

PART NUMBER R040-	NUMBER OF 40' ELEMENTS	D.A.L. IN	S Span IN
91	1	47 1/16	
92	2	87 1/8	50
93	3	127 1/8	80
94	4	167 3/16	100
95	5	207 3/16	125
96	6	247 1/4	150
99	14	21 1/16	
100	21	28 1/16	


NOTES:

- OD COATED WITH HIGH GLOSS WHITE POLYURETHANE PAINT
- DIMENSION IN INCHES
- SPAN CENTERD ON TUBE IF OPTIONAL SUPPORTS USED MUST BE USED ON 3 ELEMENT AND LONGER.

WORKING PRESSURE 600 PSI at 120°F
(4.3 MPa at 49°C)

TEST PRESSURE 900 PSI
(6.4 MPa)

MIN. OPERATING TEMP. 20°F
(-7°C)

A & M COMPOSITES CORPORATION Quality FILAMENT WOUND COMPOSITE Products		TOLERANCES (EXCEPT AS NOTED)		RO PRESSURE VESSEL	
		DECIMAL 1		SCALE 1" - 1"	DRAWN BY WC
 Phone (915)267-6525		FRACTIONAL 1	TITLE 4" - 600 psi. End Port		
		ANGULAR 1	DATE 03-07-00	DRAWING NUMBER 4-600PSI-EP	
				APPROVED BY MN	